



DIRT AND GREASE CLEANER

for PAVERS AND SLABS

2L • 20L

2 U.S. qt. • 5.25 U.S. gal.

UPDATE

May 12, 2004

Make sure that you have an up-to-date technical data sheet at hand.

Canada and U.S.A.: dial 1-800-465-7325.

Others: dial 514-523-8324 (Canada).

www.techniseal.com

FUNCTION

Dissolves, dislodges and encapsulates grease.

APPLICATIONS

- Sealed or bare surfaces.
- Pavers and slabs made of concrete or natural stone, masonry, etc.
- Concrete, clay, stone, marble, granite, slate, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, buildings, etc.

DESCRIPTION

TECHNI-SEAL DIRT AND GREASE CLEANER is the most effective product available for removing motor oil and grease (barbecue) stains from concrete or natural stone pavers and slabs. It dissolves, dislodges and encapsulates grease, thoroughly cleaning without leaving any oily film after rinsing.

DIRECTIONS

Read the Material Safety Data Sheet before using this product. Wear adequate protective clothing. On a sealed surface, wet the stain before applying product; on a bare surface, apply dry. Cover the stain generously with DIRT AND GREASE CLEANER; let work for 2 to 3 minutes; reapply product and scrub with a SMALL TECHNI-SEAL BRUSH; do not let product dry on the surface; rinse thoroughly with water. Repeat if necessary.

NOTE

An oil spot that has penetrated the material may resurface within 24 hours following cleaning; if this occurs, repeat the process. An oil stain on a light-colored surface may leave a blackish mark after cleaning; lighten the mark using PAINT, TAR AND RUBBER REMOVER (1X1-541/2X1-547) or EFFLORESCENCE CLEANER (1X1-534/2X1-537).

PACKAGING

CANADA

Product Code	Retail Size	Pro Size	Units per box	Units per pallet
141-512	2L	•	6	216
241-517	•	20L	•	24

USA

Product Code	Retail Size	Pro Size	Units per box	Units per pallet
121-512	2 qt.	•	6	216
221-517	•	5.25 gal.	•	24

WARNINGS

AVOID CONTACT WITH EYES.

FIRST AID TREATMENT: IF SWALLOWED, GIVE A GLASS OF MILK. IF SPLASHED IN EYES OR ON SKIN, FLUSH THOROUGHLY WITH WATER. CALL PHYSICIAN OR POISON CONTROL CENTRE IMMEDIATELY.

CONTAINS: TRISODIUM PHOSPHATE AND SODIUM METASILICATE.

SHIPPING

Land and Sea

Not regulated

LIMITED WARRANTY: Since it has no control over surface preparation and product application, Techni-Seal can not guarantee the results. Techni-Seal's warranty is limited to the replacement of product proven defective. Note: User should have an up-to-date technical data sheet handy and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.