



2L  
2 U.S. qt.



## RUST REMOVER

for PAVERS AND SLABS

### UPDATE

**May 12, 2004**

Make sure that you have an up-to-date technical data sheet at hand.

Canada and U.S.A.: dial 1-800-465-7325.

Others: dial 514-523-8324 (Canada).

[www.techniseal.com](http://www.techniseal.com)

### FUNCTION

Effectively removes stains caused by metal, rusted water, fertilizer, etc.

### APPLICATIONS

- Sealed or bare surfaces.
- Pavers and slabs made of concrete or natural stone, masonry, etc.
- Concrete, clay, stone, marble, granite, slate, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, buildings, etc.

### DESCRIPTION

TECHNI-SEAL RUST REMOVER takes out rust from concrete or natural stone pavers and slabs. It effectively dissolves stains caused by dripping rusted water, steel streaks, fertilizer granules<sup>1</sup>, etc. Since it contains no hydrochloric (muriatic) acid, it won't discolor the material.

<sup>1</sup>To remove fertilizer stains from a large surface, it is recommended to use TECHNI-SEAL EFFLORESCENCE CLEANER (1X1-534, 2X1-537).

**DIRECTIONS**

Read the Material Safety Data Sheet before using this product. Wear adequate protective clothing. Wet the stain and cover it generously with RUST REMOVER; using a SMALL TECHNI-SEAL BRUSH, scrub the stain until dissolved; rinse immediately with water. If rust persists, repeat the operation.

**NOTE**

Pavement with efflorescence (whitish salt) will appear spotted after the use of RUST REMOVER; for uniform results, finish by cleaning the entire surface with EFFLORESCENCE CLEANER (1X1-534/2X1-537). Rust streaks caused by snowplough rubbing may be difficult to remove.

**PACKAGING**

**CANADA**

Product Code	Retail Size	Units by box	Units per pallet
141-522	2 L	6	216

**USA**

Product Code	Retail Size	Units by box	Units per pallet
121-522	2 qt.	6	216

**WARNINGS**

**DANGER**

**CORROSIVE. CAUSES IRREVERSIBLE EYE AND SKIN DAMAGE. VAPOR EXTREMELY IRRITATING. MAY CAUSE DELAYED LUNG INJURY. HARMFUL IF SWALLOWED.**

Do not get in eyes, on skin or clothing. Avoid breathing vapor or mist. Do not take internally. Use only with adequate ventilation. Keep container closed when not in use.

**First Aid:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. If not breathing give artificial respiration and get medical attention. Wash contaminated clothing and thoroughly clean contaminated shoes before reuse. If swallowed get medical attention immediately. Do not induce vomiting unless directed to do so by medical personnel.

**Contains:** phosphoric acid. Keep out of reach of children.

**SHIPPING**

**Land and Sea**

Phosphoric Acid in Solution  
 Class : 8 (9.2)  
 UN Number : 1805  
 Packing Group : III  
 Flash Point : n/a

**LIMITED WARRANTY:** Since it has no control over surface preparation and product application, Techni-Seal can not guarantee the results. Techni-Seal's warranty is limited to the replacement of product proven defective. Note: User should have an up-to-date technical data sheet handy and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.